



LEDI[®] 1/S Remote display

7-segment LED display with high red luminescence:
Hour, minute and second



- Height of digits: 14.2 mm
 - Legibility distance: 7 meters
 - 12h or 24h mode
 - SNMP (NTP version)
 - Configurable time/date alternation
 - Brightness setting
 - AFNOR or NTP synchronization
- Saving of time information in case of power failure in the event of a power failure by built-in lithium battery
- Power supply: 230VAC 50/60Hz, class 1
 - DC power supply: 18 to 36 VDC or 36 to 72 VDC
 - Power supply: Power over Ethernet (PoE - IEEE802.3af)

- Consumption:
 - AFNOR: 3VA
 - NTP: 5VA
- Operating T°: 0° to 50°C
- Storage T°: -20° to 85°C

Aluminium case

- Display case dimensions: L160 x H44 x D26mm
Weight: 0.80 kg
- Control unit dimensions: L180 x H44 x D146mm
Weight: 0.720 kg
- Connection cable between the 2 elements: HD XGA DB15 male/male shielded cable Lg.1.8m

Standards: Safety (EN 62368), EMC (EN 55032 & EN 55035)

		ITEM CODE		
		92143	/	
VERSION		↑	↑	↑
AFNOR NFS 87500 Receiver	■	8		
Sync. NTP (RJ45)	■	N		
POWER SUPPLY				
230VAC 50/60Hz	■	0		
18 to 36 VDC	■	5		
36 to 72 VDC	■	9		
PoE (IEEE802.3af)	■	7		
FRONT FACE (Display casing)				
Front panel dimensions: 1U x 160mm	■			2
Front panel dimensions: 19"1U	■			7
Front panel dimensions on request	■			

