

LEDI® 7.S Indoor / Single face



Professional LED clock, robust and stylish combining the best of the technology for an easy installation and operation.



Time setting

The professional LEDI® clocks can display the same time information, synchronized by a master clock or a time server. On standalone and pulse version, the time setting is manual. Display date and time alternately

Internal time base

The LEDI® clock has its own temperature compensated TCXO time base which allows an accuracy about 0.1 sec / day between 0° to 40°C in case of synchronization loss.

Security

Backup of time information in case of mains absence, by lithium battery: 10 years.

Specifications


Power supply (following version)	230VAC 50/60Hz 115VAC 50/60Hz Low voltage 12, 24 or 48 VDC NTP Version: PoE (Power over Ethernet)
Certifications	CE, EN 62368, EN 55032, EN 55035, ROHS
Maximum consumption	15.06 VA
IP	30
MTBF	56 225 h
MTTR	Display: 5 min CPU: 5 min Power supply: 5 min
Weight	1.8 kg
Dimension	430x 165x62 mm (LxHxD)
Digit height	Hour/minute: 70 mm Seconds: 50 mm
Maximal distance of legibility	35 meters
Operating temperature	-20° to +50°C
Electrical equipment classification	⚡ Class 1 (in 115 or 230 VAC) ⚡ Class 3 (in 12, 24, 48 VDC or PoE)

Storage conditions

Conditions	Temperature	Hygrometry	Maximum cumulative duration
Extreme	-20°C to 10°C	10 to 85% HR	48h
Extreme	40°C to 70°C	10 to 85% HR	48h
Normal	10°C to 40°C	10 to 85% HR	6 months

The product must be switched on for 4 hours every 3 months to maintain its characteristics*.

*see user guide for more information



Key features

- Perfectly silent, direct and accurate reading of time.
- SMD bi-colour LED technology allows to change the display colour in red, green or yellow (optional white or blue)
- The patented technology of the light guide provides a perfect regularity of the brightness and viewing angle at 160°
- The front face of the LEDI® is coated with an antiglare and anti-scratch film giving an extraordinary 60000 : 1 level of contrast.
- A protection against over-voltage and industrial interference via EMC filter
- An easy "plug and play" installation
- An anodized aluminium case wall mount or flush mount
- Its participation in the sustainable development life span over 20 years.
- 2 years warranty
- Up to 10 brightness levels for optimal viewing
- Remote and batch configuration via the optional "remote configuration" software
- Selection of colours (independently between wave and numbers) and brightness
- Behaviour of central dots (fixed, blinking...)

NTP Version

Advanced version (option K)

- Synchronisation of up to 4 NTPv4 servers and setting of advanced NTP options (poll rate / burst / preference order)
 - Time zone selection and automatic summer/winter time change
 - Supervision by SNMP v1, v2c, v3, SYSLOG, Consultation of event logs
 - Configurations accessible via http and/or https
 - Possibility of changing the display colour according to events (e.g. a loss of synchronisation changes the display colour to red)
 - IPv4 / IPv6 protocoles
 - 12h or 24h Mmode
 - Stopwatch/timer: advanced options fully configurable and programmable (start time, end time, colour change...), control and configuration via web page, GTCHRONO or SNMP
 - Sensor*: Option to manage up to 3 different SNMP sensors (Temperature, Hygrometry, ...)
- *Within the limits of the display

Standard Version (option N or W)

- Synchronisation of up to 3 NTP servers
- Time zone selection and automatic summer/winter time change
- Supervision by SNMP v1, v2.c
- Configurations accessible via http and/or https
- IPv4 / IPv6 protocoles
- Stopwatch/timer: simple option (triggering of a count sequence or countdown by button via web page or SNMP)
- Sensor: option to manage an SNMP Temperature or Humidity sensor

Display / LED characteristics

Single row LED display, SMD technology, reading angle: 160°

bi-colour (red, green) LED		Monochrome LED
• Red: 245 mcd	• Yellow	• Blue: 625 mcd
• Green: 780 mcd		• White: 625 mcd

Synchronisation inputs

- TCXO Quartz Standalone
 - DCF77 (EUROPE) with antenna or DCF24V with pair cable
 - GPS
 - Reverse parallel minute receiver 24V or 1/2 reverse minute series
 - AFNOR NFS 87500 or IRIG B (to specify at purchase order)
 - ASCII RS232, ASCII RS422/485
 - Standard NTP (Option N) or advanced NTP (Option K) Ethernet 10/100BaseT
 - Standard NTP Wi-Fi (IEEE 802.11 a/b/g/n standards 2.4 Ghz)
- SMPTE

LEDI® 7.S Indoor / Single face

		ITEM CODE					
		N366					
VERSION		↑	↑	↑	↑	↑	↑
Standalone: radio-synchronisable quartz time base 3.6864 MHz Holdover +/- 0.1 sec/24 h (between 0 and 40°C) <input type="checkbox"/>		2					
DCF Radiosynchronisation. DCF Antenna + 4m cable <input type="checkbox"/>		D					
⁽¹⁾ DCF 24Vdc Synchronisation (<i>Synchro in telecom pair cable</i>) <input type="checkbox"/>		P					
GPS Radiosynchronisation. GPS Antenna + 10m cable <input type="checkbox"/>		G					
6mA/24V reversed parallel minute pulses receiver clock Serial reversed 1/2 minute pulses receiver clock Consumption 1.25V. 60 to 120mA. 39 ohms shunt <input type="checkbox"/>		3					
⁽²⁾ AFNOR NFS 87500 Receiver <input type="checkbox"/>		5					
SMPTE-EBU Receiver <input type="checkbox"/>		8					
ASCII RS 232 Receiver <input type="checkbox"/>		7					
ASCII 422/485 Receiver <input type="checkbox"/>		B					
ADVANCED NTP Synchronisation (Ethernet RJ45 10/100) <input type="checkbox"/>		Q					
STANDARD NTP Synchronisation (Ethernet RJ45 10/100) <input type="checkbox"/>		K					
STANDARD NTP Synchronisation (Wi-Fi IEEE 802.11 a/b/g/n standard 2.4 Ghz) <input type="checkbox"/>		N					
		W					
<i>(1) Always combine this version with 230VAC 50/60Hz power supply only</i>							
<i>(2) If IRIG.B. version, please specify as a note on your order</i>							
PROGRAMMABLE LED							
Selectable colour, red, yellow, green <input type="checkbox"/>		1					
Selectable colour white or blue <input type="checkbox"/>		5					
MOUNTING							
Standard: Wall mounting with bracket <input type="checkbox"/>		1					
Flush mounted <input type="checkbox"/>		3					
COLOUR CASING							
Grey anodised aluminium <input type="checkbox"/>					7		
Painted black RAL9005 Aluminium <input type="checkbox"/>					0		
POWER SUPPLY							
Standard: 230VAC 50/60Hz <input type="checkbox"/>					0		
115VAC 50/60Hz (<i>Excluding version P</i>) <input type="checkbox"/>					1		
Power over Ethernet (PoE - IEEE802.3af) (<i>version N or K</i>) <input type="checkbox"/>					7		
⁽³⁾ Low voltage power supply: 12 VDC (<i>Excluding versions K, N or W</i>) <input type="checkbox"/>					2		
⁽³⁾ Low voltage power supply: 24 VDC (<i>Excluding versions K, N or W</i>) <input type="checkbox"/>					4		
⁽³⁾ Low voltage power supply: 48 VDC (<i>Excluding versions K, N or W</i>) <input type="checkbox"/>					6		
OPTIONS							
⁽⁴⁾ Timer function via web interface (<i>versions K, N or W</i>) <input type="checkbox"/>							F
⁽³⁾ Timer: touch housing control block (flush and wall mount version) + 4 meters of cable - up/down <input type="checkbox"/>							I
⁽³⁾ Timer : touch housing control block (flush and wall mount version) + 15 meters of cable - up/down <input type="checkbox"/>							C
⁽³⁾ Temperature probe(accuracy ± 0.5°C) + 5 m cable : temperature and hour displayed alternately <input type="checkbox"/>							T
⁽⁵⁾ IP Temperature sensor module (<i>versions K, N or W</i>) <input type="checkbox"/>							G
⁽³⁾ Timer output or stopwatch contact <input type="checkbox"/>							E
⁽³⁾ ASCII RS232 output (<i>not to be combined with Ascii input version</i>) <input type="checkbox"/>							A
or: <input type="checkbox"/>							R
⁽³⁾ ASCII RS422-485 output (<i>not to be combined with Ascii input version</i>) <input type="checkbox"/>							
Tropicalization <input type="checkbox"/>							U

⁽³⁾ Option not available in NTP versions (Ethernet or Wi-Fi)

⁽⁴⁾ CDG035 – GT Chrono compatible: Only for NTP Advanced Ethernet version (option K), management of the triggering of groups of clocks simultaneously and synchronised, by Windows software.

⁽⁵⁾ Option for NTP versions (Ethernet or Wi-Fi) only, and compatible with a Temperature Sensor via IP station to be ordered separately, see module 92261